


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:220.70V I:0.3120A P:67.300W PF:0.9760 Freq:50.00Hz Lamp Flux:11058.1x1 lm		
Name: LSD-M 1200 68W 4000K	Type: 长条形	
MFR.:	DIM.: 1202*64*85mm	
	SUR.: 1192*60mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 164.31 lm/W			
MODEL		Imax(cd)	9450	S/MH(C0/180)	0.98
NOMINAL POWER(W)	68	LOR(%)	100.0	S/MH(C90/270)	1.00
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	11058	η UP,DN(C0-180)	1.2,46.8
NOMINAL FLUX(lm)	11058.1	CIE CLASS	DIRECT	η UP,DN(C180-360)	1.4,50.6
LAMPS INSIDE	1	η up(%)	2.6	CIBSE SHR NOM	1.00
TEST VOLTAGE(V)	220.8	η down(%)	97.4	CIBSE SHR MAX	1.05

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PLANAR ISOLUX DIAGRAM(UNIT:lx)



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-10-17

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED: 2835-LT2-0800C1R540(F),
PCB: LSD-M 1200-82S2P+16-V2.0(A+B),
电源: SC65W160-280CG-4HV

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	9173	9131	9091	9029	9141	9187	9248	9257	0- 10	887.3	887.3	8.02,8.02
20	8271	8174	8003	8004	8227	8305	8361	8459	10- 20	2469	3356	30.4,30.4
30	5838	6045	5471	5796	5912	6280	5950	6524	20- 30	3337	6694	60.5,60.5
40	2325	2749	2271	2563	2525	3014	2735	3209	30- 40	2715	9409	85.1,85.1
50	328.4	534.8	357.4	478.3	394.2	660.2	460.6	737.8	40- 50	1089	10498	94.9,94.9
60	51.26	72.86	56.45	70.16	96.22	97.90	73.66	101.9	50- 60	213.0	10711	96.9,96.9
70	5.397	8.781	9.873	8.083	15.87	20.85	23.25	21.04	60- 70	30.01	10741	97.1,97.1
80	4.523	6.375	7.567	6.279	16.67	19.62	21.57	19.60	70- 80	13.90	10755	97.3,97.3
90	6.716	7.851	8.126	8.180	21.15	22.54	22.37	22.44	80- 90	15.13	10770	97.4,97.4
100	13.15	14.14	15.63	14.87	28.19	28.65	29.09	28.20	90-100	19.49	10790	97.6,97.6
110	23.82	24.77	26.29	25.63	36.61	37.34	37.94	36.58	100-110	27.54	10817	97.8,97.8
120	37.66	38.00	38.93	39.10	46.69	47.58	47.81	46.69	110-120	36.49	10854	98.2,98.2
130	53.08	52.45	52.13	53.48	58.57	58.50	57.78	57.60	120-130	43.95	10898	98.6,98.6
140	66.81	65.33	63.89	65.93	69.93	68.52	66.53	67.17	130-140	47.33	10945	99,99
150	76.23	73.97	73.25	75.16	77.40	76.50	73.69	73.81	140-150	44.60	10990	99.4,99.4
160	81.92	81.21	81.21	81.50	81.38	82.48	80.38	79.49	150-160	36.05	11026	99.7,99.7
170	89.18	87.97	87.26	86.78	88.66	88.07	86.24	85.34	160-170	23.80	11050	99.9,99.9
180	93.73	91.69	89.99	89.55	93.77	91.71	89.98	89.55	170-180	8.491	11058	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-10-17

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity:65.0%
Test Distance:8.000m [K=0.7063]
Remarks: LED:2835-LT2-0800C1R540(F),
PCB:LSD-M 1200-82S2P+16-V2.0(A+B),
电源: SC65W160-280CG-4HV

LUMINANCE LIMITATION CURVES

Test:U:220.70V I:0.3120A P:67.300W PF:0.9760 Freq:50.00Hz Lamp Flux:11058.1x1 lm		
Name: LSD-M 1200 68W 4000K	Type: 长条形	
MFR.:	DIM.: 1202*64*85mm	
	SUR.: 1192*60mm	



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-10-17

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED: 2835-LT2-0800C1R540(F),
PCB: LSD-M 1200-82S2P+16-V2.0(A+B),
电源: SC65W160-280CG-4HV

```

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity:65.0%
Test Distance:8.000m [K=0.7063]
Remarks: LED:2835-LT2-0800C1R540(F),
          PCB:LSD-M 1200-82S2P+16-V2.0(A+B),
          电源: SC65W160-280CG-4HV

```

WEC AND CCEC

Test:U:220.70V I:0.3120A P:67.300W PF:0.9760 Freq:50.00Hz		
Lamp Flux:11058.1x1 lm		
Name: LSD-M 1200 68W 4000K	Type: 长条形	
MFR.:	DIM.: 1202*64*85mm	
	SUR.: 1192*60mm	

ρ_{cc}	80%			70%			50%			30%			10%			0	
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ_{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.191	.108	.034	.183	.104	.033	.169	.097	.031	.156	.090	.029	.144	.083	.027		
2.0	.183	.101	.031	.177	.097	.030	.165	.092	.028	.154	.086	.027	.143	.081	.026		
3.0	.175	.093	.028	.170	.091	.027	.159	.086	.026	.150	.082	.025	.141	.078	.024		
4.0	.167	.087	.026	.162	.085	.025	.153	.081	.024	.145	.078	.023	.137	.074	.023		
5.0	.160	.081	.024	.155	.080	.023	.147	.077	.023	.140	.074	.022	.132	.071	.021		
6.0	.152	.076	.022	.148	.075	.022	.141	.072	.021	.134	.070	.021	.128	.067	.020		
7.0	.145	.072	.020	.142	.071	.020	.136	.069	.020	.129	.066	.019	.124	.064	.019		
8.0	.139	.068	.019	.136	.067	.019	.130	.065	.019	.125	.063	.018	.119	.061	.018		
9.0	.133	.064	.018	.130	.063	.018	.125	.062	.018	.120	.060	.017	.115	.059	.017		
10.0	.127	.061	.017	.125	.060	.017	.120	.059	.017	.116	.057	.016	.111	.056	.016		

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.210	.210	.210	.180	.180	.180	.123	.123	.123	.070	.070	.070	.023	.023	.023	
1.0	.192	.177	.164	.164	.152	.141	.112	.105	.097	.065	.061	.057	.021	.019	.018	
2.0	.178	.153	.131	.152	.131	.113	.104	.091	.079	.060	.053	.046	.019	.017	.015	
3.0	.166	.134	.108	.143	.116	.094	.098	.080	.066	.057	.047	.039	.018	.015	.013	
4.0	.157	.119	.091	.135	.103	.079	.093	.072	.056	.054	.042	.033	.017	.014	.011	
5.0	.149	.108	.078	.128	.094	.068	.088	.065	.048	.051	.038	.028	.016	.013	.009	
6.0	.142	.099	.068	.122	.086	.060	.084	.060	.042	.049	.035	.025	.016	.012	.008	
7.0	.136	.092	.061	.117	.080	.053	.081	.056	.038	.047	.033	.022	.015	.011	.007	
8.0	.130	.086	.055	.112	.074	.048	.078	.052	.034	.045	.031	.020	.015	.010	.007	
9.0	.125	.081	.051	.108	.070	.044	.075	.049	.031	.044	.029	.019	.014	.010	.006	
10.0	.121	.076	.047	.104	.066	.041	.072	.047	.029	.042	.028	.017	.014	.009	.006	

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-10-17

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED:2835-LT2-0800C1R540(F),
 PCB:LSD-M 1200-82S2P+16-V2.0(A+B),
 电源: SC65W160-280CG-4HV

UGR(Unified Glare Rating) Table

Test:U:220.70V I:0.3120A P:67.300W PF:0.9760 Freq:50.00Hz Lamp Flux:11058.1x1 lm		
Name: LSD-M 1200 68W 4000K	Type: 长条形	
MFR.:	DIM.: 1202*64*85mm	
	SUR.: 1192*60mm	

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	19.5	20.6	19.8	20.8	21.0	19.4	20.4	19.6	20.6	20.8
3H	19.4	20.3	19.7	20.5	20.8	19.2	20.1	19.5	20.4	20.6
4H	19.3	20.1	19.6	20.4	20.7	19.1	20.0	19.4	20.2	20.5
6H	19.2	20.0	19.5	20.3	20.6	19.0	19.8	19.3	20.1	20.4
8H	19.1	19.9	19.5	20.2	20.5	18.9	19.7	19.3	20.0	20.3
12H	19.1	19.8	19.4	20.1	20.5	18.9	19.6	19.3	20.0	20.3
4H 2H	19.3	20.1	19.6	20.4	20.7	19.1	20.0	19.4	20.2	20.5
3H	19.1	19.8	19.4	20.1	20.5	18.9	19.7	19.3	20.0	20.3
4H	19.0	19.7	19.4	20.0	20.4	18.8	19.5	19.2	19.8	20.2
6H	18.9	19.5	19.3	19.8	20.3	18.7	19.3	19.1	19.7	20.1
8H	18.8	19.4	19.3	19.8	20.2	18.7	19.2	19.1	19.6	20.0
12H	18.8	19.3	19.2	19.7	20.1	18.6	19.1	19.1	19.5	20.0
8H 4H	18.8	19.4	19.3	19.8	20.2	18.7	19.2	19.1	19.6	20.0
6H	18.7	19.2	19.2	19.6	20.1	18.6	19.0	19.0	19.4	19.9
8H	18.7	19.1	19.2	19.5	20.0	18.5	18.9	19.0	19.4	19.9
12H	18.6	19.0	19.1	19.4	20.0	18.5	18.8	19.0	19.3	19.8
12H 4H	18.8	19.3	19.2	19.7	20.1	18.6	19.1	19.1	19.5	20.0
6H	18.7	19.1	19.2	19.5	20.0	18.5	18.9	19.0	19.4	19.9
8H	18.6	18.9	19.1	19.4	20.0	18.5	18.8	19.0	19.3	19.8
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 2.6 / -13.0					+ 2.6 / -12.4				
1.5H	+ 4.5 / - 9.8					+ 4.4 / - 8.7				
2.0H	+ 6.2 / -12.8					+ 6.0 / -11.3				

CIE Pub.117, 11058 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 8.3$)
Area: 0.0715 m²

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-10-17

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity:65.0%
Test Distance:8.000m [K=0.7063]
Remarks: LED:2835-LT2-0800C1R540(F),
PCB:LSD-M 1200-82S2P+16-V2.0(A+B),
电源: SC65W160-280CG-4HV

UTILIZATION FACTORS TABLE

Test:U:220.70V I:0.3120A P:67.300W PF:0.9760 Freq:50.00Hz Lamp Flux:11058.1x1 lm		
Name: LSD-M 1200 68W 4000K	Type: 长条形	
MFR.:	DIM.: 1202*64*85mm	
	SUR.: 1192*60mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	82	75	71	81	75	71	80	74	70	66
0.80	90	84	79	89	83	79	88	82	79	74
1.00	96	89	85	95	89	85	93	89	84	80
1.25	100	94	91	99	94	90	97	92	89	84
1.50	103	98	94	102	97	94	99	95	92	87
2.00	107	102	98	105	101	97	102	98	96	90
2.50	108	104	101	107	103	100	103	100	98	91
3.00	110	106	103	108	105	102	104	102	100	92
4.00	112	109	107	110	107	105	106	104	102	94
5.00	114	111	109	111	109	107	107	105	104	95
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2023-10-17

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity:65.0%
Test Distance:8.000m [K=0.7063]
Remarks: LED:2835-LT2-0800C1R540(F),
PCB:LSD-M 1200-82S2P+16-V2.0(A+B),
电源: SC65W160-280CG-4HV

ISOCANDELA DIAGRAM

Test:U:220.70V I:0.3120A P:67.300W PF:0.9760 Freq:50.00Hz Lamp Flux:11058.1x1 lm		
Name: LSD-M 1200 68W 4000K	Type: 长条形	
MFR.:	DIM.: 1202*64*85mm	
	SUR.: 1192*60mm	




C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-10-17

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED: 2835-LT2-0800C1R540(F),
PCB: LSD-M 1200-82S2P+16-V2.0(A+B),
电源: SC65W160-280CG-4HV

AAI Figure

Test:U:220.70V I:0.3120A P:67.300W PF:0.9760 Freq:50.00Hz Lamp Flux:11058.1x1 lm		
Name: LSD-M 1200 68W 4000K	Type: 长条形	
MFR.:	DIM.: 1202*64*85mm	
	SUR.: 1192*60mm	

Flux out:7943 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-10-17

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED: 2835-LT2-0800C1R540(F),
PCB: LSD-M 1200-82S2P+16-V2.0(A+B),
电源: SC65W160-280CG-4HV

ISOLUX DIAGRAM


Test:U:220.70V I:0.3120A P:67.300W PF:0.9760 Freq:50.00Hz Lamp Flux:11058.1x1 lm		
Name: LSD-M 1200 68W 4000K	Type: 长条形	
MFR.:	DIM.: 1202*64*85mm	
	SUR.: 1192*60mm	



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-10-17

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED: 2835-LT2-0800C1R540(F),
PCB: LSD-M 1200-82S2P+16-V2.0(A+B),
电源: SC65W160-280CG-4HV

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-10-17

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED: 2835-LT2-0800C1R540(F),
PCB: LSD-M 1200-82S2P+16-V2.0(A+B),
电源: SC65W160-280CG-4HV

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.70V I:0.3120A P:67.300W PF:0.9760 Freq:50.00Hz Lamp Flux:11058.1x1 lm		
Name: LSD-M 1200 68W 4000K	Type: 长条形	
MFR.:	DIM.: 1202*64*85mm	
	SUR.: 1192*60mm	

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	30	60	90	120	150	180	210	240	270	300	330						
0	9450	9440	9431	9424	9417	9420	9450	9440	9431	9424	9417	9420						
5	9383	9367	9342	9326	9293	9293	9366	9370	9394	9408	9415	9404						
10	9173	9148	9114	9091	9031	9027	9141	9155	9218	9248	9274	9240						
15	8813	8776	8722	8691	8615	8609	8773	8802	8881	8932	8970	8935						
20	8271	8226	8121	8003	7987	8021	8227	8272	8337	8361	8463	8454						
25	7420	7459	7149	6878	6993	7221	7421	7529	7454	7344	7620	7746						
30	5838	6275	5815	5471	5648	5944	5912	6380	6180	5950	6378	6671						
35	4031	4479	4285	3943	4136	4154	4184	4605	4688	4389	4872	4930						
40	2325	2762	2736	2271	2593	2533	2525	2918	3110	2735	3266	3152						
45	895	1380	1332	916	1241	1226	1050	1521	1675	1254	1796	1690						
50	328	547	523	357	484	473	394	614	707	461	772	704						
55	168	185	210	181	193	173	210	223	265	201	282	243						
60	51.3	67.9	77.9	56.4	71.3	69.1	96.2	93.4	102	73.7	107	96.4						
65	8.47	13.7	16.5	13.5	15.3	13.3	20.7	29.6	32.4	27.8	34.0	30.8						
70	5.40	7.80	9.76	9.87	9.01	7.15	15.9	19.1	22.5	23.2	22.7	19.4						
75	4.41	6.19	7.84	8.13	7.41	5.87	15.5	18.0	20.8	21.7	21.0	18.1						
80	4.52	5.63	7.12	7.57	6.95	5.61	16.7	18.5	20.7	21.6	20.8	18.4						
85	5.19	6.12	7.58	8.22	7.60	6.41	18.6	20.1	21.8	22.5	21.7	19.9						
90	6.72	7.34	8.36	8.13	8.50	7.86	21.1	22.1	23.0	22.4	22.9	21.9						
95	9.46	9.69	10.8	11.4	11.2	10.5	24.5	24.9	25.2	25.4	24.9	24.6						
100	13.1	13.5	14.8	15.6	15.3	14.4	28.2	28.6	28.7	29.1	28.3	28.1						
105	18.0	18.3	19.7	20.7	20.4	19.3	32.3	32.7	32.9	33.3	32.3	32.0						
110	23.8	24.1	25.5	26.3	26.2	25.1	36.6	37.2	37.5	37.9	36.8	36.3						
115	30.5	30.5	31.8	32.4	32.6	31.7	41.5	42.1	42.5	42.8	41.8	41.1						
120	37.7	37.5	38.5	38.9	39.4	38.8	46.7	47.5	47.7	47.8	46.9	46.4						
125	45.2	45.0	45.4	45.5	46.3	46.3	52.5	53.1	52.8	52.8	52.2	52.0						
130	53.1	52.7	52.2	52.1	53.1	53.9	58.6	59.0	58.0	57.8	57.3	57.9						
135	60.3	60.0	58.4	58.3	59.3	60.7	64.4	64.5	62.7	62.4	61.8	63.5						
140	66.8	66.6	64.1	63.9	65.1	66.8	69.9	69.6	67.4	66.5	66.0	68.3						
145	72.4	71.8	69.0	68.8	70.2	71.9	74.3	74.1	71.6	70.3	69.6	72.2						
150	76.2	75.0	72.9	73.3	74.6	75.7	77.4	77.8	75.2	73.7	72.6	75.0						
155	78.8	78.2	76.7	77.4	78.4	78.7	79.2	80.7	78.4	77.1	75.7	77.5						
160	81.9	81.8	80.6	81.2	81.8	81.2	81.4	83.4	81.6	80.4	78.9	80.1						
165	85.4	85.4	84.1	84.6	84.7	83.7	84.5	86.2	84.5	83.5	82.1	82.9						
170	89.2	88.7	87.3	87.3	87.2	86.4	88.7	88.9	87.2	86.2	85.0	85.7						
175	92.3	91.4	89.7	89.2	89.0	88.7	92.1	91.3	89.4	88.5	87.6	88.1						
180	93.7	92.7	90.7	90.0	89.4	89.7	93.8	92.7	90.8	90.0	89.5	89.7						

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2023-10-17

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.443
Humidity: 65.0%
Test Distance: 8.000m [K=0.7063]
Remarks: LED: 2835-LT2-0800C1R540(F),
PCB: LSD-M 1200-82S2P+16-V2.0(A+B),
电源: SC65W160-280CG-4HV