


WALL LIGHT





Moon M502 is a masterpiece of ambient lighting, especially for deluxe places like hotel, museum, art gallery.

- 1 • Reserved BESA holes, Key holes • Cable entry from side and back • Through wiring from side to side
- 2 • IP54 water-proof • IK10 vandal-proof
- 3 • Optional selectable power
- 4 • Ceiling/wall mounted, or installed in suspension
- 5 • Wide choice of intelligent functions, with/without Bluetooth, sensor, DALI, etc.


Dynaluxx existing product Moon M320 can be upgrade with color tray to become this aesthetics ambient light




WALL LIGHT



Dimension



Photometrics



Lumen Output

Model	Power	3000K	4000K	5000K
		85 lm/W	90 lm/W	95 lm/W
M502	12W	1050 lm	1110 lm	1130 lm
M502	18W	1530 lm	1580 lm	1660 lm
M502	28W	2550 lm	2700 lm	2750 lm

• Lumen may fluctuate between ± 10%. Customized higher lumen output available.

Specification

Input Voltage	220-240VAC	Fitting Material	PC + Aluminum
CRI	>80	Electrical Class	II
Power Factor	>0.9	Standard Lifespan	L70B50: 64,000h
SDCM	3	Premium Lifespan	L70B50: 148,000h L80B10: 78,000h
Beam Angle	120°	Standard	EN60598-2-1 / EN55015 / EN62778
Operation Temp.	-20°C ~ +40°C		
IP Rating	IP54		
IK Rating	IK10		

Order Code

• Subject to change without notice. Please scan the QR code for complete code list.

Code	Model	Power	On/Off	Microwave	PIR	BT	EME	DAL	RFD	RFM	CCT	Efficiency	Dimension (mm)
M00012	M502	18W	●								40K	90 lm/W	ø 502 * H 84